



NESSCAP® Ultracapacitor Products

Features

Module
Compliant with RoHS requirement (Ex : Cd, Pb)
Active + passive cell voltage balancing
205F/42V(17 series of 2.7V/3500F Cells) : 8 series 2 parallel

Dimension

Dimension in mm (not to scale)



Capacitance	Dimension (mm)		
	L (max)	W (max)	T (max)
51F	1568	276	960

Product & Spec.

Rated Capacitance	Internal Resistance (mΩ)		Max. Current (A)	Leakage Current (mA)	Stored Energy (Wh)	Specific Energy (Wh/kg)	Weight (kg)	Part Number
	Discharge with constant current at 25°C	AC(100Hz)						
51F	< 19	< 24.5	3,854	N/A	818.833	2.13	384	EMHSP-0051C0-340R0

Rated Voltage, V_R	340.0 V	
Surge Voltage	367.2 V	
Capacitance Tolerance	0% / +20%	
Operating Temperature Range	-40 ~ 65 °C	ΔC <5% and ΔESR < 0.5 times of initially measured value at 25°C, respectively
Storage Temperature Range	-40 ~ 70 °C	
Life Time at RT ⁽¹⁾	10 years	(1) ΔC < 30% and ΔESR < 1 times of initially specified value, respectively and LC < specified value
Cycle Life (25°C) ⁽¹⁾⁽²⁾	500,000 cycles	(2) Cycle : between rated voltage and half rated voltage under constant current at 25°C

* Life time is provisional value

© NESSCAP 2008. All Rights reserved. Design, Specifications are subjected to change without notice.